


# Data sheet

Sensor-switched LED floodlight

## XLED CAM 1

EAN 4007841065294



### Function description

Security the smart way. Sensor-switched floodlight XLED CAM 1 (3000 K, 2200 lm, 21 W) with 180° infrared motion sensor and 10 m reach, swivelling HD wide-angle colour camera and intercom system. Delivers excellent surveillance images directly to the mobile device. Includes 8 GB SD card for storing the surveillance images. Free app for iOS and Android.

### Technical specifications

Dimensions (L x W x H)	167 x 210 x 275 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,00 m
Sensor Technology	passive infrared
Output	21 W
Interconnection	No
Luminous flux	2200 lm
Colour temperature	3000 K
With lamp	Yes, LED lamp
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
With motion detector	Yes
Detection angle	180 °
Angle of aperture	45 °
Twilight setting	10 – 10000 lx
Time setting	60 s – 15 Min.
IP rating	IP44
Protection class	I

# Data sheet



Sensor-switched LED floodlight

## XLED CAM 1

EAN 4007841065294

### Technical specifications

Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Manufacturer's Warranty	3 years
PU1, net weight	1,471 kg
PU1, EAN	4007841065294

### Mood image

