


# Data sheet

## Floodlight

# Spot Garden

Sensor Connect

EAN 4007841058685



## Function description

Interconnected garden enjoyment. The Spot Garden Sensor Connect ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 520 lm, 7 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

## Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	7 W
Slave modeselectable	Yes
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index CRI	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Capability of masking out individual segments	No
Reach, radial	passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m²)

# Data sheet

## Floodlight

# Spot Garden

Sensor Connect

EAN 4007841058685

### Technical specifications

Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Functions	Manual ON / ON-OFF
Continuous light	selectable, 4h
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	0,710 kg
Version	Sensor Connect
PU1, EAN	4007841058685

### Mood image

