

Data sheet




Sensor-switched LED floodlight

Spot Way

Sensor Connect

EAN 4007841058661



Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 520 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,50 m
Sensor Technology	passive infrared
Output	7 W
Slave modeselectable	Yes
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index CRI	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Capability of masking out individual segments	No
Reach, radial	passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m²)

Data sheet

Sensor-switched LED floodlight

Spot Way

Sensor Connect

EAN 4007841058661

Technical specifications

Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Functions	Manual ON / ON-OFF
Continuous light	selectable, 4h
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	1,230 kg
Version	Sensor Connect
PU1, EAN	4007841058661

Mood image

