


Sensor-switched LED floodlight

## XLED ONE XL Sensor

Anthracite

EAN 4007841065263



### Function description

Powerful illumination. Effective protection. The XLED ONE XL Sensor wall and ceiling spot can be tilted through 180° and illuminates its surroundings with day-bright light. In numbers: 3000 K and 4400 lm from 43,5 W. With infrared sensor, 180° angle of coverage, 12 m reach, twilight setting (2-2000 lux) as well as time setting (8 s to 35 min). Protection class: IP44.

### Technical specifications

Dimensions (L x W x H)	222 x 259 x 215 mm
Mains power supply	230 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	43,5 W
Luminous flux	4400 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	No
Capability of masking out individual segments	Yes

# Data sheet

Sensor-switched LED floodlight

## XLED ONE XL Sensor

Anthracite

EAN 4007841065263

### Technical specifications

Reach, radial	r = 3 m (14 m <sup>2</sup> )
Reach, tangential	r = 10 m (157 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Basic light level function	No
IP rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Manufacturer's Warranty	3 years
PU1, net weight	1,396 kg
Version	Anthracite
PU1, EAN	4007841065263

### Mood image

